



NOTES:

- 250 WATT HIGH PRESSURE SODIUM LUMINAIRE WITH A MOUNTING HEIGHT OF 12.2 METRES. LIGHT POLES ARE TO BE LOCATED ON THE SHOULDER ROUNDING. POLE BASE LOCATION AND ORIENTATION SHALL BE AS SHOWN.
- TYPICAL DELINEATION LIGHTING LOCATIONS. TWO LUMINAIRES ARE REQUIRED WHERE ROAD WIDTH EXCEEDS THREE LANES ON ANY APPROACH. ORIENT LUMINAIRES DIAGONALLY ACROSS THE WIDEST DIMENSION OF THE INTERSECTION.
- FOR FURTHER LIGHTING DETAILS SEE FILE NUMBERS: S-2009-094, S-2009-111 THROUGH S-2009-116.
- LENGTH MAY VARY TO REFLECT SITE SPECIFIC DESIGN REQUIREMENTS.
- WIDENING FOR LEFT TURN LANE CAN BE ON ONE SIDE OF CENTERLINE, DEPENDING ON AVAILABLE RIGHT OF WAY, ADJACENT LAND DEVELOPMENT, AND HORIZONTAL ALIGNMENT OF MAJOR ROAD.
- MAY BE SHORTENED DEPENDING ON DESIGN SPEED OF MAJOR ROAD.
- ALL DIMENSIONS ARE IN METERS UNLESS OTHERWISE NOTED.

**NOVA SCOTIA**  
Transportation and Infrastructure Renewal

No.	REVISION

Scale : N.T.S.  
Drawn by : J.MACINTOSH  
Checked by : K.BODDY  
Date of Plan : AUG2009  
File No. : S-2009-038

*Adrian Colburn*  
Manager Highway Planning and Design

*[Signature]*  
Director Highway Engineering Services

*[Signature]*  
Executive Director Highway Engineering and Construction

**'FOUR-LEG' INTERSECTION**  
**SCHOOL BUS OR WB-12 DESIGN VEHICLE**