Canada

GEOLOGICAL SURVEY OF CANADA
COMMISSION GÉOLOGIQUE DU CANADA
DEPARTMENT OF ENERGY, MINES AND RESOURCES
MINISTÈRE DE L'ÉNERGIE, DES MINES ET DES RESSOURCES

MOLYBDENUM

Nova Scotia Department of Mines and Energy

11 K/15 — 1:50 000 — CANADA — EDITION 3 — 11 K/15

Mo

LEGEND

Sample number ..... e.g. ● 82 – 1 – 025 (year; location; group; sequential number)

Analytical value in p.p.m. (unless otherwise specified)... e.g. ● 106

Geochemical Sample Medium

- Stream sediment, sieved ..... ●
- Stream sediment, unsieved ..... ○
- Lake sediment ..... ◘
- Heavy mineral / panned concentrate ..... ⊕
- Soil ..... □
- Rock ..... ◇
- Peat ..... △
- Till ..... ■
- Other ..... ⊠

Note: Two (2) sample numbers per sample location indicates duplicate sample site... e.g. ● 82-1-025,026

HISTOGRAM AND BASIC STATISTICS



Note: Only data within this 1:50,000 sheet is included.

Average:	1.26
Number of samples:	135.
Standard deviation:	0.06
Range:	1.00 – 5.00
Detection limit:	2 ppm

Sample collection and Geochemistry: P.J. Rogers and M.A. MacDonald
Analyses: Chemex Laboratories Ltd., North Vancouver, B.C.
Sample digestion: Hot HNO_3 – HCL Extraction
Analytical technique: Nitrous Oxide – Acetylene AAS

Produced by the SURVEYS AND MAPPING BRANCH, DEPARTMENT OF ENERGY, MINES AND RESOURCES. Updated from aerial photographs taken in 1978. Colour check 1979. Published in 1981.

Copies may be obtained from the Canada Map Office, Department of Energy, Mines and Resources, Ottawa, or your nearest map dealer.

© 1981 Her Majesty the Queen in Right of Canada
Department of Energy, Mines and Resources.

Roads: hard-surface, all-weather — paved, double lanes; hard-surface, all-weather — paved, single lane; loose or stabilized surface, all-weather — gravel, improved, double lanes; loose surface, dry weather — dirt, single lane; unclassified streets; trail; trail or private portage.

Railroads: double track; single track; narrow gauge; narrow gauge on a portage.

Road numbers: 2-digit numbers (Arterial); 3-digit numbers (Primary); 4-digit numbers (Secondary); 5-digit numbers (Local).

FOR COMPLETE REFERENCE SEE REVERSE SIDE — POUR UNE LISTE COMPLÈTE DES SIGNES VOIR AU VERSO

PLEASANT BAY
NOVA SCOTIA

Scale 1:50 000 Échelle

Miles 1 — 0 — 1 — 2 — 3 Miles
Metres 1000 — 0 — 1000 — 2000 — 3000 — 4000 Metres
Yards 1000 — 0 — 1000 — 2000 — 3000 — 4000 Yards

Information concerning location and precise elevation of benchmarks can be obtained by writing to the Geodetic Survey, Surveys and Mapping Branch, Ottawa.

CONVERSION SCALE FOR ELEVATIONS
Metres 0 10 20 30 40 50 60 70 80 90 100 Metres
Feet 0 50 100 150 200 250 300 350 400 450 500 550 600 650 700 750 800 850 900 950 1000 Feet

CONTOUR INTERVAL 50 FEET
Elevations in Feet above Mean Sea Level
North American Datum 1927
Transverse Mercator Projection

Où pour obtenir des renseignements sur le repère: latitude exacte des repères de nivellement en accord avec l'avis géodésique. Direction des levés et de la cartographie, Ottawa.

ECHELLE DE CONVERSION DES ALTITUDES

ÉQUIDISTANCE DES COURBES 50 PIEDS
Altitudes en pieds
Système de référence géodésique nord-américain 1927
Projection transverse de Mercator

Établie par la DIRECTION DES LEVÉS ET DE LA CARTOGRAPHIE, MINISTÈRE DE L'ÉNERGIE, DES MINES ET DES RESSOURCES. Mise à jour à l'aide de photographies aériennes prises en 1978. Vérification des couleurs en 1979. Publiée en 1981.

Ces cartes sont en vente au Bureau des Cartes du Canada, ministère de l'Énergie, des Mines et des Ressources, Ottawa, ou chez le vendeur le plus près.

© 1981 Sa Majesté la Reine du Chef du Canada
Ministère de l'Énergie, des Mines et des Ressources.

OPEN FILE
DOSSIER PUBLIC
986
Geological Survey
Commission Geologique
Ottawa

CONTRIBUTION TO CANADA – NOVA SCOTIA
CO-OPERATIVE MINERAL PROGRAM 1981-84

OPEN FILE
OFM 84-12
Nova Scotia
Department of
Mines and Energy