



NOTES:

1. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE NOTED.
2. DIMENSIONS ARE MEASURED PERPENDICULAR TO CENTERLINE.
3. TO BE ADJUSTED TO ALLOW FOR MINIMUM OF 5.0m BEYOND DAYLIGHT LOCATION OR EXCEPTIONALLY 3.0m MAY BE ACCEPTABLE.
4. THE SUBGRADE WIDTH IS DEPENDENT UPON THE DEPTH OF STRUCTURAL MATERIAL.
5. 0.4m ROUNDING CENTERED ON SHOULDER BREAK POINT IF GUARDRAIL NOT INSTALLED.
6. 0.0m PAVED SHOULDER TYPE FOR AADT < 5000; 0.2m PAVED SHOULDER TYPE FOR AADT > 5000.
7. DITCH WIDTH TO BE BASED ON HYDRAULIC PERFORMANCE.

No.	REVISION

Scale : N.T.S.
 Drawn by : G.WRIGHT
 Checked by : K.BODDY
 Date of Plan : NOV-2015
 File No. : S-2015-007

B. W. ...
 Manager Highway Planning and Design
...
 Director Highway Engineering Services
...
 Executive Director Highway Engineering and Construction

STANDARD CROSS SECTION MAJOR COLLECTOR (E)