



- NOTES: 1. ALL DIMENSIONS ARE IN METRES UNLESS OTHERWISE NOTED.  
 2. DIMENSIONS ARE MEASURED PERPENDICULAR TO CENTERLINE.  
 3. TO BE ADJUSTED TO ALLOW FOR MINIMUM OF 5.0m BEYOND DAYLIGHT LOCATION OR EXCEPTIONALLY 3.0m MAY BE ACCEPTABLE.  
 4. THE SUBGRADE WIDTH IS DEPENDENT UPON THE DEPTH OF STRUCTURAL MATERIAL.  
 5. 0.6m ROUNDING CENTERED ON SHOULDER BREAK POINT IF GUARDRAIL NOT INSTALLED.  
 6. DITCH WIDTH TO BE BASED ON HYDRAULIC CAPACITY.  
 7. A WIDER PAVED SHOULDER WILL BE REQUIRED IF RUMBLE STRIPS ARE BEING USED - REFER TO P01055

*Redilip Singh*  
 Manager Highway Planning and Design

*David Wood*  
 Director Highway Engineering Services

*John Kelly*  
 Executive Director Highway Engineering and Construction



No.	REVISION

Scale : N.T.S.  
 Drawn by : G.WRIGHT  
 Checked by : K.BODDY  
 Date of Plan : NOV-2015  
 File No. : S-2015-043

**STANDARD CROSS SECTION  
 MINOR ARTERIAL TYPE (C) (D)**