



- NOTES:
1. THE SPACING OF POSTS AT ENDS, CORNERS AND GATES SHALL BE $\leq 2.5m$. ALL OTHER POSTS SHALL BE SPACED $\leq 5.0m$ APART.
 2. WIRES SHALL BE STRETCHED TAUT AND FASTENED SECURELY TO POSTS AS DIRECTED BY THE ENGINEER WITH APPROVED 40mm GALVANIZED STAPLES.
 3. END, CORNER AND GATE POSTS SHALL BE FIRMLY BRACED WITH DIAGONALS EXTENDING FROM A POINT ON THE POST AT THE ELEVATION OF THE TOP FENCE WIRE TO A POINT ABOUT 150mm ABOVE THE GROUND LEVEL ON THE ADJACENT POST.
 4. POSTS SHALL BE SLIGHTLY FLATTENED AT THE JUNCTION WITH THE BRACE.
 5. MINIMUM CROSS SECTION OF BRACES SHALL BE 125mm DIAMETER OR 100mm SQUARE.
 6. STAY WIRES SHALL BE FASTENED SECURELY TO EACH POST WITH 40mm GALVANIZED STAPLES AND TWISTED TOGETHER TAUT.
 7. DOUBLE STAY WIRES NO. 9 GAUGE (PLAIN) SHALL BE STRETCHED FROM A POINT ABOUT 150mm ABOVE THE GROUND LEVEL ON END, GATE AND CORNER POSTS TO A POINT ON THE ADJACENT POST AT THE ELEVATION OF THE TOP FENCE WIRE.
 8. POST LENGTHS: FOR FABRIC WIDTHS $> 1.8m$ THE POST SHALL BE INCREASED BY THE AMOUNT OF THE DIFFERENCE.
 9. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE NOTED.

NOVASCOTIA
Transportation and Infrastructure Renewal

No.	1	HS #	ADDED TO TITLE
REVISION			

Scale : N.T.S.
 Drawn by : M.LABRECHE
 Checked by : K.BODDY
 Date of Plan : AUG2009
 File No. : S-2009-025

Director Highway Engineering Services
 Manager Highway Planning and Design
Philip Chiu
 Executive Director Highway Engineering and Construction
RIGHT-OF-WAY FENCE
HS-601